

Office Pro® 36

Your Local Source for Portable Cooling



Providing 36,000 performance-verified Btu/h of cooling, the Office Pro 36 is the ideal cooling solution for servers, routers, telecom and other heat-sensitive equipment. The Office Pro 36 features easy-to-use programmable controls allowing automatic operation after-hours or during weekends when heat can cause damage to expensive office equipment.

The Office Pro 36 makes portable air conditioner solutions a breeze through its self-contained, portable design. No costly installation is necessary. Just roll it in. Plug it in. Turn it on. It's that simple.

- Low temperature operation ideal for cooling heat-sensitive equipment
- Offers an optional "Plug and Play" condensate pump that can be installed in just minutes
- Protected with an LCDI plug for added safety against the unwanted effects of electrical arcing
- Totally self-contained with no costly installation necessary
- Operates automatically after-hours or during weekends with easy-to-use controls



MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

Toll Free: 877-823-2722

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



TECHNICAL SPECS

OFFICE PRO® 36*

Electronic Features	Control	Programmable
Cooling Capacity	Rating Conditions: 95°F at 60% RH	36,000 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	1 Phase, 208/230V 4.3 kW 19.6 amps 30 amps 6 - 30 198 - 250
Fans	Motor Output - high/low	0.21/0.13 kW (Evaporator) 0.33/0.12 kW (Condenser)
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 990/825 CFM 0.6 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 1490/1060 CFM 0.5 IWG
Compressor	Type Output	Hermetic Scroll 2.3 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	30 x 44 x 52 in
Net Weight/Shipping Weight		440/483 lb
Power Cord	Gauge/Length	12 AWG (3-core)/6 ft
Condensate Tank Capacity		2 @ 5 gal
Operating Conditions	Min. – Max. (@ 50% RH)	65° - 95°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	40 ft 60 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	65/62 dB(A) 67/66 dB(A)

* Specification information shown with 230V
All specifications subject to change without notice.

© 2013 DENSO SALES CALIFORNIA, INC. MovinCool, SpotCool and Office Pro are registered trademarks of DENSO Corporation.
360-0213-OP36

