

Classic Plus 26

MOVINCOOL®
THE #1 SPOT COOLING SOLUTION

The MovinCool Classic Plus 26 portable air conditioner has all the benefits of our proven Classic Series, PLUS new features designed to increase performance and control. The versatile Classic Plus is instantly ready to provide cool air in the hottest environments such as production lines, outdoor events, manufacturing processes, injection molding, metal forming and much more.

The Classic Plus features a programmable digital temperature controller allowing the user to "set" the desired temperature. By cooling only the area that needs it, the Classic Plus 26 portable air conditioner saves you money while protecting people and equipment and speeding up processes. Self-contained and portable, the Classic Plus 26 requires little or no installation—simply roll it in, plug it in and turn it on.

- Programmable digital temperature control, set the desired temperature and walk away
- Totally self-contained with no costly installation necessary
- Handles temperatures up to 113°F, provides cooling in the hottest environments
- Provides up to 24,000 Btu/h of cool air, maximum cooling to just the spot that needs it



MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

800.264.9573
www.movincool.com

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



TECHNICAL SPECS

CLASSIC PLUS 26*

| | | |
|-----------------------------|---|--|
| Electronic Features | Control | Programmable |
| Cooling Capacity | Rating Conditions: 95°F at 60% RH | 24,000 Btu/h |
| Electrical Characteristics | Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage | 1 Phase, 208/230V 3.1 kW 14.0 amps 20 amps 6 - 20 198 - 250 |
| Fans | Motor Output - high/low | 0.55/0.38 kW |
| Evaporator | Fan Type Max. Air Flow - high/low Max. External Static Pressure | Centrifugal 708/600 CFM 0.54 IWG |
| Condenser | Fan Type Max. Air Flow - high/low Max. External Static Pressure | Centrifugal 1680/1460 CFM 0.25 IWG |
| Compressor | Type Output | Hermetic Scroll 1.5 kW |
| Refrigerant | Type | R-410A |
| Dimensions | W x D x H | 19 x 29 x 47 in |
| Net Weight/Shipping Weight | | 235/265 lb |
| Power Cord | Gauge/Length | 12 AWG (3-core)/6 ft |
| Condensate Tank Capacity | | 5 gal |
| Operating Conditions | Min. – Max. (@ 50% RH) | 70° - 113°F |
| Max. Equivalent Duct Length | Per Cold Duct Hose Hot Duct Hose | 60 ft 45 ft |
| Max. Sound Level | With Condenser - Duct high/low Without Condenser - Duct high/low | 66/64 dB(A) 69/67 dB(A) |

* Specification information shown with 230V

All specifications subject to change without notice.

© 2013 DENSO SALES CALIFORNIA, INC. MovinCool, SpotCool and Office Pro are registered trademarks of DENSO Corporation.

360-0213-CP26

