

# Classic 10

Your Local Source for Portable Cooling



At home in an office or in the warehouse, the Classic 10 portable air conditioner is the original portable air conditioner. It has no special power requirement so the Classic 10 can be rolled into any room and it's instantly ready to cool the hottest spot. By cooling only the area that needs it, the Classic 10 saves you money while protecting people and equipment and speeding up processes.

Self-contained and portable, the Classic 10 requires little or no installation, simply roll it in, plug it in and turn it on.

- Provides 10,000 Btu/h of cool air
- Operates on standard 115V. Roll it into any room that needs it
- Handles temperatures up to 105°F. Provides cooling in the hottest environments
- Half the cost of central air conditioning, cooling for as little as 15 cents per hour
- Rugged design, proven durability since 1982



# MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

Toll Free 1-877-823-2722

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



## TECHNICAL SPECS

## CLASSIC 10

Electronic Features	Control	Digital
Cooling Capacity	Rating Conditions: 95°F at 60% RH	10,000 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	1 Phase, 115V 1.1 kW 10 amps 15 amps 5 - 15 105 - 125
Fans	Motor Output - high/low	0.15 kW
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 265 CFM 0.33 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 740 CFM 0.13 IWG
Compressor	Type Output	Hermetic Rotary 0.7 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	19 x 26 x 41 in
Net Weight/Shipping Weight		156/194 lb
Power Cord	Gauge/Length	14 AWG (3-core)/10 ft
Condensate Tank Capacity		5 gal
Operating Conditions	Min. – Max. (@ 50% RH)	70° - 105°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	40 ft 60 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	53 dB(A) 58 dB(A)

All specifications subject to change without notice.

© 2013 DENSO SALES CALIFORNIA, INC. MovinCool, SpotCool and Office Pro are registered trademarks of DENSO Corporation.

360-0213-C10

