



## Climate Pro X Series

The cooler choice for your warehouse or factory.

The all-new Climate Pro X Series brings advanced spot-cooling to commercial and industrial applications—perfect for cooling people and production processes.

### Key Features

- Air-cooled units from 13,200 to 24,000 Btu/h — to handle temps as high as 113°F
- Three-speed fan and adjustable nozzles for versatile cooling comfort
- New! 115 V/20 amp model (16,800 Btu/h)
- Digital controls and auto operation — for 24/7 programmable back-up of central systems.
- Effective moisture removal — hastens drying for humid and water-damaged areas.
- Connectivity ready with remote monitoring, geolocation and performance notifications.\*



### Ideal for . . .

Warehouses  
Assembly Lines  
Manufacturing Plants  
Process Cooling  
Construction Sites  
Moisture Removal  
Outdoors and Events



## Climate Pro X Series Specifications



		X14	X20	X26
Electronic Features	Control Panel	Programmable	Programmable	Programmable
Cooling Capacity	Rating Conditions: 95°F @ 60% RH	13,200 Btu/h	16,800 Btu/h	24,000 Btu/h
Electrical Characteristics	Voltage Requirement (60 Hz)	1 Phase, 115 V	1 Phase, 115 V	1 Phase, 208/230 V
	Total Power Consumption	1.3 kW	1.7 kW	2.7 kW*
	Current Consumption	11.5 amps	15.5 amps	12.8 amps*
	Recommended Fuse Size	15 amps	20 amps	20 amps
	NEMA Plug Configuration	5-15P	5-20P	6-20P
	Min. Max. Voltage	104 – 127 V	104 – 127 V	198 – 253 V
Fans	Motor Output	0.23 kW	0.37 kW	0.56 kW
Evaporator	Fan Type	Centrifugal	Centrifugal	Centrifugal
	Max Air Flow - High/Mid/Low	440/410/385 CFM	565/525/475 CFM	700/650/595 CFM
	Max External Static Pressure	0.31 IWG	0.31 IWG	0.42 IWG
Condenser	Fan Type	Centrifugal	Centrifugal	Centrifugal
	Max Air Flow - High/Mid/Low	830/770/720 CFM	890/835/760 CFM	1475/1370/1260 CFM
	Max External Static Pressure	0.19 IWG	0.23 IWG	0.25 IWG
Compressor	Type	Hermetic Rotary	Hermetic Rotary	Hermetic Rotary
	Output	0.75 kW	0.9 kW	1.5 kW
Refrigerant	Type	R-410A	R-410A	R-410A
Dimensions	W x D x H	22 x 29 x 48 in	22 x 29 x 51 in	22 x 29 x 51 in
Net Weight/Shipping Weight		165/205 lb	195/237 lb	216/256 lb
Power Cord	Gauge	14 AWG (3 -core)	12 AWG (3-core)	12 AWG (3-core)
	Length	10 ft	10 ft	6 ft
Condensate Tank Capacity		5 gal	5 gal	5 gal
Operating Conditions	Min. – Max. @ 50% RH	70° – 113°F	70° – 113°F	70° – 113°F
Max. Duct Length	Per Cold Duct Hose	30 ft	30 ft	60 ft
	Hot Duct Hose	60 ft	60 ft	45 ft
Max. Sound Level	With Condenser Duct - High/Mid/Low	57/56/55 dB(A)	64/63/62	66/65/64 dB(A)
	Without Condenser Duct - High/Mid/Low	60/59/58 dB(A)	67/66/65	69/68/67 dB(A)

\*Specifications information shown with 230V. All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit [MovinCool.com/warranty](http://MovinCool.com/warranty) for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

Toll Free 877-823-2722



American Portable Air